



LAUGFS
LUBRICANTS

BRAKE & CLUTCH FLUID



PRODUCT DESCRIPTION

BRAKE & CLUTCH FLUID is designed for use in conventional hydraulic brake and clutch systems under normal service conditions, particularly where DOT 3 fluids are recommended.

USER BENEFITS AND PRODUCT FEATURES

- Enhanced brake performance
- Reduces maintenance requirements
- Minimizes leakage and loss of pressure
- Longer fluid service life

PRODUCT APPLICATIONS

- All hydraulically operated motor vehicle braking systems (drum and disc types) requiring DOT 3 or SAE J1703 fluid
- Vehicles equipped with anti-lock braking (ABS) systems
- Hydraulic clutch systems requiring conventional fluids
- Suitable for passenger cars, commercial road transport, off-highway vehicles, agricultural tractors, and motorcycles

PRODUCT RECOMMENDATIONS AND APPROVALS

- OEM recommendations and Performance meets

DOT-3/SAE J1703

PHYSICAL AND CHEMICAL PROPERTIES

Parameter	Test Method	Test data
Viscosity Grade	-	SAE 10W
Appearance	Visual	Bright & Clear
ASTM Colour	ASTM D1500	Max 2.0
Kinematic Viscosity @ -40°C, cSt	ASTM D445	1400
Kinematic Viscosity @ 100°C, cSt	ASTM D445	2.8
pH value	ASTM D7946	8.4

*This is a technical Specification for LAUGFS Product according to the current additive package. It may have minor deviations on basis of supply.

ENVIRONMENT, HEALTH and SAFETY, is available in the material safety data sheet (MSDS) of the product. Customers are encouraged to review the information, follow precautions and comply with laws and regulations concerning product use and disposal.



- 🏠 LAUGFS LUBRICANTS LTD
- 📍 101, Maya Avenue, Colombo 06, Sri Lanka
- ☎ +94 11 556 6222
- ✉ info@laugfslubricants.com
- 🌐 www.laugfslubricants.com