



# LAUGFS LUBRICANTS

## LUBREX RED 2 EP2 GREASE NLGI GC - LB



### PRODUCT DESCRIPTION

LAUGFS LUBREX RED 2 is a premium extreme-pressure (EP) NLGI 2 grease designed for a wide range of automotive, construction, wheel bearing, and chassis lubrication applications. It is formulated with high-quality mineral base oils and a lithium complex thickener, enhanced with EP additives, rust inhibitors, and oxidation stabilizers. It performs exceptionally under EP conditions, providing extended equipment life and reliable protection.

### USER BENEFITS AND PRODUCT FEATURES

- **Reduced Maintenance Cost:**  
Advanced EP additives provide strong protection against bearing wear, even under extreme conditions and shock loads. Rust and corrosion inhibitors safeguard metal surfaces, ensuring durability even in severe water exposure environments.
- **Reduced Downtime:**  
A high dropping point prevents bearing leakage at elevated temperatures, while excellent oxidation resistance extends grease life.
- **Multi-Purpose Applications:**  
Versatile formulation supports a wide range of automotive and industrial uses, reducing the need for multiple grease types and minimizing the risk of product misapplication.

### PRODUCT APPLICATIONS

- Automotive wheel bearings and chassis lubrication for both highway and off-highway applications
- Construction equipment, agricultural tractors, heavy-duty transport, and industrial greasing applications

# PRODUCT RECOMMENDATIONS AND APPROVALS

NLGI GC-LB

## PHYSICAL AND CHEMICAL PROPERTIES

Parameter	Test Method	Test data
Colour	Visual	Red
Thickener type	Formulation	Lithium Complex
NLGI Grade	ASTM D217	2
Worked penetration after 60 double strokes @ 25 °C	ASTM D217	265 - 295
Dropping point, °C	ASTM D2265	240
Copper corrosion	ASTM D4048	1b
Base oil, KV @ 40 °C, cSt	ASTM D445	160
Fretting Protection ,mass loss, mg, max	ASTM D4170	9 <sup>B</sup>
Water Resistance at 80 °C,% wt	ASTM D1264	4.5
Oil Separation, % wt	ASTM D1742	3.3
Rust Protection, rating	ASTM D1743	PASS
Wear protection, scar diameter, mm	ASTM D2266	0.49
EP performance 4 Ball Weld Load, kgf	ASTM D2596	200

\*This is a technical Specification for LAUGFS Product according to the current additive package. It may have minor deviations on basis of supply.

ENVIRONMENT, HEALTH and SAFETY, is available in the material safety data sheet (MSDS) of the product. Customers are encouraged to review the information, follow precautions and comply with laws and regulations concerning product use and disposal.



- LAUGFS LUBRICANTS LTD
- 101, Maya Avenue, Colombo 06, Sri Lanka
- +94 11 556 6222
- info@laugfslubricants.com
- www.laugfslubricants.com