



LAUGFS
LUBRICANTS

POWER

SAE 10W D10

**MULTI - PURPOSE HYDRAULIC
& POWER SHIFT
TRANSMISSION FLUID**



PRODUCT DESCRIPTION

POWER D10W is a premium multi-purpose hydraulic and power-shift transmission fluid formulated with highly refined base oils and a balanced additive system, selected to meet industry-specific lubrication requirements.

USER BENEFITS AND PRODUCT FEATURES

- **Extended Working Life:**
Formulated with highly refined paraffinic mineral oils and a technologically advanced additive system to reduce component wear and extend fluid life
- **Good Thermal and Oxidation Stability:**
Superior oxidation stability helps prevent oil degradation and thickening
- **Improved Cold-Temperature Performance:**
Highly refined mineral oils and additives provide excellent performance in low temperatures

PRODUCT APPLICATIONS

- Hydraulic systems and components where the oil type and viscosity grade are suitable
- Power-shift transmissions and hydraulic systems
- Power transmission systems of construction equipment, agricultural tractors, and other similar applications requiring the appropriate viscosity grade

PHYSICAL AND CHEMICAL PROPERTIES

Parameter	Test Method	Test value
Appearance	Visual	B&C
ASTM Color	ASTM D1500	2.5-3.0
Kinematic Viscosity @ 40°C, cSt	ASTM D445	32.10
Kinematic Viscosity @ 100°C, cSt	ASTM D445	5.57
Viscosity Index	ASTM D2270	110
Flash Point (COC), °C	ASTM D92	225
Pour point , °C	ASTM D97	-21
Base Number, mg KOH/g	ASTM D2896	6.0

*This is a technical Specification for LAUGFS Product according to the current additive package. It may have minor deviations on basis of supply.

ENVIRONMENT, HEALTH and SAFETY, is available in the material safety data sheet (MSDS) of the product. Customers are encouraged to review the information, follow precautions and comply with laws and regulations concerning product use and disposal.



- LAUGFS LUBRICANTS LTD
- 101, Maya Avenue, Colombo 06, Sri Lanka
- +94 11 556 6222
- info@laugfslubricants.com
- www.laugfslubricants.com