

VELOMATIC

**AUTOMATIC TRANSMISSION AND POWER
STEERING FLUID**

DEXRON-III



PRODUCT DESCRIPTION

LAUGFS VELOMATIC ATF, a new generation petroleum based product for automatic and power shift transmissions. The highest level product of ATF are suitable for use both GM Dexron III with 6297-M and Ford Mercon specification M2C185A. In addition, it also meets Allison C-4 fluid and is qualified as a PSF specification. LAUGFS VELOMATIC ATF provide superior wear protection for all passenger car and light trucks requiring the use of TASA, Dexron II D, Dexron II E or Dexron III G/H/M ATFs.

USER BENEFITS AND PRODUCT FEATURES

- Provides prompt and reliable lubrication in both high and low temperature operating condition
- Enhanced protection against wear to prolong transmission life
- Improved cleanliness of transmission system
- Exceptional thermal and oxidation stability
- Proven compatibility with elastomer

PRODUCT APPLICATIONS

- Automatic Transmission Fluids are recommended for mobile equipment used by utility companies, which require electrical insulating properties for hydraulic oils
- Passenger cars and light truck automatic transmissions, on-highway heavy duty transmission applications requiring Dexron III performance level
- Power steering system where the manufacture recommends a Dexron III fluid Off-Highway power transmission requiring Allison C-4
- Mobile, industrial and marine hydraulic systems (where a Dexron III type is required)
- Any other transmission system for which Dexron, Dexron II or Dexron III oil is recommended

PRODUCT RECOMMENDATIONS AND APPROVALS

SAE Viscosity Grade

SAE 10W

Performance Standards
meets & exceeds

DEXRON III H
DEXRON III M
DEXRON III G
DEXRON II E
DEXRON II D
Ford ESP-M2C138-CJ
Ford ESP-M2C166-H
MERCON-M2C185A
ALLISON C-4
ALLISON C-3
PSF (Power steering Fluid)
TASA
Cat TO-2

PHYSICAL AND CHEMICAL PROPERTIES

Parameter	Test Method	Test value
Appearance	Visual	Red
Density @ 30 °C, g/mL	ASTM D4052	0.84
Kinematic Viscosity @ 40 °C,cSt	ASTM D445	34.47
Kinematic Viscosity @ 100 °C,cSt	ASTM D445	7.10
Viscosity Index	ASTM D2270	175
Flash point (COC), °C	ASTM D92	198
Pour point, °C	ASTM D97	-45

*This is a technical Specification for LAUGFS Product according to the current additive package. It may have minor deviations on basis of supply.

ENVIRONMENT, HEALTH and SAFETY, is available in the material safety data sheet (MSDS) of the product. Customers are encouraged to review the information, follow precautions and comply with laws and regulations concerning product use and disposal.



LAUGFS LUBRICANTS LTD
101, Maya Avenue, Colombo 06, Sri Lanka
+94 11 556 6222
info@laugfslubricants.com
www.laugfslubricants.com